

**CS205****10-Hour Fuel Temperature Stick (without sensor)**

Precision-Made Ponderosa Pine Dowel

Overview

The CS205 is a hollowed-out ponderosa-pine dowel that emulates the temperature of similarly sized twigs on the forest floor. Fuel temperature is measured by inserting the

thermistor-based 107 probe inside the CS205 dowel. The CS205 and 107 probe are often incorporated in our prewired or custom fire-weather stations.

Benefits and Features

- › Companion product to CS506 fuel moisture sensor; can be mounted on the same stake
- › Used with the 107 probe to measure fuel temperature for forest fire applications

Detailed Description

The CS205's ponderosa pine dowel is fabricated to US Forest Service specifications, but with a hole bored into one end. Dowel replacement is recommended every spring; more frequent replacement may be required in some environments

(i.e., those with a large number of wet/dry cycles). The CS205 is easily replaced in the field using a Phillips screwdriver and an adjustable wrench.

Specifications

Material	Ponderosa Pine	Length	11.4 cm (4.5 in.)
Diameter	1.3 cm (0.5 in.)	Weight	9.07 g (0.32 oz) for stick only

For comprehensive details, visit: www.campbellsci.com.au/cs205 



Campbell Scientific Australia | 411 Bayswater Road | Garbutt, QLD 4814 | +61 (0)7 4401 7700 | www.campbellsci.com.au
 AUSTRALIA | BRAZIL | CANADA | CHINA | COSTA RICA | FRANCE | GERMANY | THAILAND | SOUTH AFRICA | SPAIN | UK | [USA](#)

© 2018 Campbell Scientific, Inc. | 06/19/2018