



## Radar Sensor Type SEBAPuls 8/15/30/20/120

for contact free measuring of surface water level

- Radar sensors for non-contact level measurement in flowing waters, lakes, reservoirs and retention basins
- Measurement ranges and accuracy:  
0-8 m ( $\pm 5$  mm), 0-15 m ( $\pm 2$  mm), 0-30 m ( $\pm 2$  mm), 0-35 m ( $\pm 2$  mm), 0-120 m ( $\pm 5$  mm)
- Protection class IP 66 / IP 68
- With adjustable mounting bracket (100 mm 300 mm and customized) for mounting on bridges, outriggers, piers and walkways



# Radar Sensor Type SEBAPuls 8/15/30/20/120

### Measuring principle:

The devices emit a continuous radar signal through their antennas. The emitted signal is reflected by the medium and received as an echo by the antenna.

The frequency difference between the emitted and received signal is proportional to the distance and depends on the filling height. The determined filling height is converted into a respective output signal and output as measured value.

### 80 GHz technology:

The 80 GHz technology used enables a unique focusing of the radar beam and a wide dynamic range of the radar sensors. The greater the dynamic range of a radar sensor, the wider its application spectrum and the higher its measurement reliability.

### Advantages:

Non-contact radar technology is characterized by extremely high measurement accuracy. The measurement is influenced neither by fluctuating product features nor by changing pro-



cess conditions such as temperature, pressure or strong dust generation. The user-friendly adjustment without vessel filling and emptying saves time.

## Technical data

Type:	SEBAPuls 8:	SEBAPuls 15:	SEBAPuls 30:	SEBAPuls 20:	SEBAPuls 120:
<b>Measuring range:</b>	0 - 8 m	0 - 15 m	0 - 30 m	0 - 35 m	0 - 120 m
<b>Accuracy:</b>	± 5 mm	± 2 mm	± 2 mm	± 2 mm	± 5 mm
<b>Material:</b>	PVDF	PVDF	PVDF	PVDF	PVDF
<b>Protection class:</b>	IP 66 / IP 68	IP 66 / IP 68	IP 66 / IP 68	IP68	IP 68
<b>Dimensions:</b>	ø 68 mm, Length: 109 mm	ø 68 mm, Length: 109 mm	ø 76 mm, Length: 130 mm	ø 115 mm, Length: 245 mm	Ø 115 mm, Length: 245 mm
<b>Output:</b>	4 ... 20 mA	4 ... 20 mA, Modbus, SDI-12, RS-485	4 ... 20 mA, Modbus, SDI-12, RS-485	4 ... 20 mA, Modbus, SDI-12, RS-485	4 ... 20 mA, Modbus, SDI-12, RS-485
<b>Operating conditions:</b>	-40 ... 60 °C 0-100% RH	-40 ... 80 °C 0-100% RH	-40 ... 80 °C 0-100% RH	-40 ... 80 °C 0-100% RH	-40 °C ... 80 °C 0-100% RH

*The right is reserved to change or amend the foregoing technical specification without prior notice*

### Contact:

SEBA Hydrometrie GmbH & Co. KG • Gewerbestraße 61 A • 87600 Kaufbeuren • Germany  
 Telefon: +49 (0) 8341 96 48 - 0 • E-Mail: info@seba.de • Web: www.seba.de