

DATASHEET

MODEL HP80 HYDROGEN PEROXIDE ANALYZER



FEATURES

- **Panel Mounted System**, Easy Installation
- **Plumb and Play Design**, Ready to Use
- **Multiple HP ranges**, 0-200 ppm or 0-2000 ppm
- **pH measurement (or others, ORP, pION, Cond) for added process information**
- **Automatic Flow Control**, Eliminates Pressure Regulators and Rotameters
- **T80 Transmitter Capability**, Dual Measurements, 24VDC or 110/220 VAC Power, Graphical Plots



SPECIFICATIONS

SENSORS AND FLOW TRAIN

Hydrogen Peroxide Sensor:

Digital protocol, Polarographic, Gold/Silver, micro-porous membrane

pH Sensor:

Digital S80 protocol, 316L stainless steel body with replaceable electrode cartridge

Measurement Range:

Hydrogen Peroxide: 0 to 200 ppm
(0 to 2000 ppm, 2%, 20% optional)

pH: 0 to 14 pH

Interferences:

Cl₂, PAA, O₃ must not be present

Sulfides contaminate measuring system.

Phenol >3% destroys sensor membrane

Operating Temperature:

0° C to 50° C (32° F to 122° F)

Min/Max Flow:

38 L/hr. to 300 L/hr. (10 gal/hr. to 80 gal/hr.)

Wetted Materials:

PVC, PP, PVDF, PTFE, Glass, 316 SS

Process Connections:

Input ¼" FNPT with barb fitting, Drain ¾" FNPT

Response Time:

T90 in 2 minutes

Electrolyte Life:

Up to 12 months



HP80 ANALYZER

Measurements:

Hydrogen Peroxide: 0 to 200 ppm or 0 to 2000 ppm, (0 to 2000 ppm, 2%, 20% optional) auto ranging

pH: 0.00 to 14.00 pH

pH Compensation: none, measurement between 2-11 pH

Display:

128 x 64 pixels (2.75" x 1.5") LCD, Black on Grey background, Blue on White background with LED backlight on

Outputs:

(1) 4-20 mA for Hydrogen Peroxide set to Sensors Range

(1) 4-20 mA for pH (Optional) set 0-14 pH

Modbus RTU (standard)

Alarm Relay Ratings:

Three (3) SPDT, 1 form C, 250 VAC, 10 Amp resistive maximum, relays, user configurable as Hi/Lo alarms with expiration timer, Periodic Timers or Fault alarms

Input Power

Code -1 24 VDC (18-36 VDC @ 250 mW minimum)

Code -2 100-240 VAC, 50/60 Hz, 4W, protected with 250V, 1A, Slow Blow fuse

Enclosure:

Beige Polycarbonate, IP65, weatherproof, ½ DIN, (L x W x D) 5.7" X 5.7" X 3.5" (14.4cm X 14.4cm X 9.0cm)

Environmental Conditions:

Outdoor use (IP65)

Ambient Temperature

-20°C - 70°C (24 VDC Models)

-20°C - 60°C (100-240 VAC Models)

Storage Temperature

-30°C - 85°C

Relative Humidity

0 – 80%, up to 31°C

Decreasing linearly to 50% RH at 40°C

Altitude

Up to 2000 m (6500 ft)

Mains Supply Voltage

Fluctuations up to ±10% of the nominal voltage

Transient over voltages: CAT II

Pollution Degree: 2